

Specifications

Headrail

Sturdy roll formed metal, 2.264" width x 2.019" height x .002" thick.

Bottomrail

Sturdy extruded PVC solid trapezoid of downward flat 2.264" (width of upper flat 1.28") x .787" height.

Slat

Plain finish Faux wood .114" thick x 1.969" width.

Valance

Plain finish Faux wood crown valance 0.570" Thick x 3.25" width.

Tape Roller Support

Injection molded plastic with Metal roller minimizing cord fray.

Tape Roller

Injection molded plastic With ladder locking legs.

Tilt Rod

Plated steel square shape. 0.248" x 0.248".

Cordlock

Zinc plated metal cordlock, metal rivet for added strength.

Tilter

Zinc plated metal housing with injection molded plastic wheel.

Bottomrail Anchors

Injection molded plastic.

Cord

Braided polyester .063" diameter.

Ladder

Braided polyester 2.126" spacing x 1.772" height.

Center Support

Plated steel.

Tassel

Injection molded plastic.

Mounting Bracket

Painted steel with hinged locking front cover.

Customization

Call for Current Pricing

Blinds measuring 11" in width can be cut up to 1/4"

Width up to 13" can be cut up to 1/2"

16"-18" in width can be cut up to 1-1/2"

19" and wider can be cut up to 4".

Packaging

36" or below: 4 per carton

37"-47": 3 per carton

48" wide and larger: 2 per carton